

“HIMELON® flame retardant ULA-E4 Series” Specifications
(難燃ヒメロン®ULA-E4シリーズ製品規格)

January 28, 2020
 AMBIC CO., LTD.
 アンビック株式会社
 Quality Assurance Section
 品質保証課

* Himelton ULA-E4 series is a product that complies with RoHS and ELV directives.

(ヒメロンULA-E4シリーズは、RoHS指令、ELV指令適合製品です。)

* Conform to FMVSS302

(FMVSS302 適合)

* UL-94 V-0 certified UL File No.E65448

(UL-94 V-0 認証済 UL File No.E65448)

* Material component :Rayon/Flame retardant fiber/Acrylic resin/Flame retardant/Coloring agent

(素材:レーヨン/難燃繊維/アクリル樹脂/難燃剤/顔料)

Products 製品名	Thickness 厚さ	Mass per unit area 目付	Weight 重さ	Tensile Strength 引張強度(N/50mm)		Width 幅		Length 長さ	
	mm	g/m ²	kg/Roll	MD	CD	mm		m	
N9491E	(0.25)	66.0 +18.4 -17.6	(3.3)	>19	>15	1000	+15 -0	50	+1.0 -0
N9591E	(0.35)	80.0 +20.3 -19.4	(4.1)	>29	>22	1000	+15 -0	50	+1.0 -0
N9592E	(0.45)	100.0 +24.6 -22.4	(5.1)	>53	>43	1000	+15 -0	50	+1.0 -0
N9691E	(0.55)	125.0 +34.5 -26.7	(6.3)	>73	>56	1000	+15 -0	50	+1.0 -0
N9791E	(0.70)	180.0 +45.0 -34.5	(9.1)	>86	>70	1000	+15 -0	50	+1.0 -0
N9891E	(0.90)	230.0 +57.4 -42.1	(11.7)	>132	>102	1000	+15 -0	50	+1.0 -0

* The standard items and numerical values listed are items and numerical values that we set to manage the product.

In addition, () notation is a reference value also in management.

(記載の規格項目・数値は、弊社が当該製品を管理するために設けた項目・数値です。なお、()表記は管理上でも参考値です。)

* This specifications is created for the purpose of providing information to customers, and does not guarantee the contents.

(本製品規格はお客様への情報提供を目的に作成しており、記載内容を保証するものではありません。)